Eaton 500MMT

Catalog Number: 500MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 500A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

General specifications

Product Name

Eaton Bussmann series high speed British standard fuse

EAN

5027590049481

Product Height 40 mm

Product Weight 469 g

Compliances CE Marked RoHS Compliant

500MMT

Catalog Number

UPC 051712835589

Product Length/Depth 98 mm

Product Width 97 mm

Warranty Not Applicable

Certifications

UL Recognized IEC Rated Designed and tested to BS88 part 4 IEC 60269-4 UL recognized





Electrical data

Amperage Rating

500 A

Voltage rating 690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

42000

Clearing (I2T)

300000

Watt losses

64 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips) TI700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

Resources

Brochures eaton-bussmann-series-bs88-high-speed-fuses-product-aidpa135003en-us.pdf

Catalogs IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports DA-DC-00004682 DA-DC-00004685

Compliance information UKCA Low voltage fuse-links *AET,*AEET,*AFEE etc

Technical data sheets 720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia